

TurbiGuard **How to order?**



Communication

IO: 0/4 ... 20 mA

Modbus RTU

Profibus DP

Profinet IO

1 TurbiGuard		
1x TurbiGuard for medium/high turbidity		
with 1x device cable 20 m	without blanking plate, with 1x device cable 10 m	without blanking plate, without device cable
		
123353	123352	118674
123355	123354	122715
		122716
		122717

Supplied without VARINLINE® installation housing, can be ordered separately.



Communication

IO: 0/4 ... 20 mA
Modbus RTU

Profibus DP

PoE – Power over
Ethernet – Web-Server
& Modbus-TCP

4 TurbiGuard + SiDis AD40
1x TurbiGuard for medium/high turbidity
1 blanking plate, with 1x connection cable 5 m

123371
123372
123373

TurbiGuard (Yeast management)



Communication

IO: 0/4 ... 20 mA

Modbus RTU

Profibus DP

Profinet IO

TurbiGuard mit SiCon	
1x TurbiGuard for medium/high turbidity + 1x SiCon	
1x blanking plate 1x connection cable 10 m	without blanking plate 1x connection cable 10 m
	
122722	122718
122723	122719
122724	122720
122725	122721

Supplied without VARINLINE® installation housing, can be ordered separately.



Communication

IO: 0/4 ... 20 mA

Modbus RTU

Profibus DP

Profinet IO

System for controlling the yeast pitching (2x TurbiGuard, SiCon M)		
2x TurbiGuard + 1x SiCon M		
+ 2 blanking plates + 2x connection cables 10 m	without blanking plate + 2x connection cables 10 m	without blanking plate Without cable
		
122734	122730	119427
122735	122731	122727
122736	122732	122728
122737	122733	122729